



THE IMPOSSIBLE MADE POSSIBLE.













THE IMPOSSIBLE MADE POSSIBLE.

From perfecting the rotary engine and winning Le Mans the first time we entered it, to breaking the world record for the most-sold two-seater convertible in history, Mazda has a long history of making the impossible possible. We are driven forward by the desire to defy convention and we believe that if you can imagine it, we can make it happen. This desire is the fuel behind everything we create and achieve and now it has given us SKYACTIV TECHNOLOGY, 'KODO - Soul of Motion' design and countless other successes that were once considered impossible feats. These pages show how striving to do what others cannot, is not only rewarding but also integral to creating innovative, beautiful cars.

MOVES YOU FROM THE FIRST LOOK.

Innovative technology, exciting performance and stunning presence. The dynamic style of the All-New Mazda3 is the result of 'KODO - Soul of Motion' design. KODO captures the moment energy becomes motion. It's the powerful grace of an animal pouncing, or a human leaping into action. This athleticism is expressed with elegance, allowing the All-New Mazda3 to make a premium impression.







The elegant cabin is precisely crafted. It carefully locates controls and information to keep you focused on the road ahead.

The Active Driving Display, available in selected models, helps to enhance concentration by projecting key data into your line of sight.

Through the use of intuitive technology, the All-New Mazda3 connects you more closely to the driving enjoyment. It boasts a large central screen that displays system information at eye-level, giving you direct access to your audio system and Bluetooth connectivity.

screen that displays system information at eye-level, giving you direct access to your audio system and Bluetooth connectivity.

Available from the Active model and above.



SKYACTIV TECHNOLOGY. HIGHER PERFORMANCE, YET GREATER FUEL ECONOMY.

The All-New Mazda3 will have drivers smiling more than ever. It dials up sports performance, yet also achieves exceptional fuel economy. This is possible because, for the first time, Mazda3 has integrated the full suit of SKYACTIV TECHNOLOGY. It's a breakthrough innovation that completely re-engineers every aspect of the vehicle to heighten performance and unleash greater efficiency. Clever features like i-stop available on the 2.0 litre engine, save you even more fuel by turning off the engine when you come to a halt and restarting it the instant you want to move.





SKYACTIV-CHASSIS


We've re-examined every component to strengthen the sense of 'oneness' between car and driver. For nimble handling and refinement, the lightweight front strut and rear multi-link suspension uses firmer bushings and totally revised geometry. Innovative welding of the front and rear cross members achieves impressive stiffness with low weight. Fuel-saving electric power-assisted steering features a high ratio for quick handling, yet delivers great stability at all speeds.





2.0 LITRE PETROL ENGINE (SKYACTIV-G)

A fundamental redesign of the internal combustion engine lifts performance while cutting fuel consumption by up to 25% over the previous model. The SKYACTIV-G engine features precise, multi-hole, direct injection to minimise fuel use, while a unique piston design enhances fuel combustion - boosting power and lowering emissions. Reduced friction unlocks extra power, while a 4-2-1 exhaust layout improves efficiency. The 2.0 litre 4-cylinder engine produces 121kW of power and 210Nm of torque, using as little as 5.8 litres of fuel every 100km.




SKYACTIV-BODY

New-generation design and materials achieve amazing lightness and rigidity. The underbody's straight-frame construction runs uninterrupted through the framework to boost stiffness and save weight. Key joints are strengthened by advanced techniques that require no heavy reinforcement. The employment of high and ultra-high tensile steel cuts weight, bolsters rigidity and aids safety. We've worked tirelessly to save every gram. Despite being light, the All-New Mazda3 disperses crash energy in multiple directions to achieve collision performance that is world-class.



AUTOMATIC TRANSMISSION (SKYACTIV-DRIVE)

We've combined the best aspects of conventional automatic with our continuously variable and dual clutch transmissions. So you get maximum driving fun and high efficiency. The SKYACTIV-Drive transmission couples directly with the engine over a far wider range than other automatics. This delivers a significant increase in fuel economy and a more direct, manual transmission-like power delivery and driving feel. Shifts are smooth, quick and accurate across the 6-speeds.



MANUAL TRANSMISSION (SKYACTIV-MT)

The manual transmission gives you the wrist-flicking shift-feel of a sports car, like our iconic Mazda MX-5. Its simplified internal design, plus a finely-honed shift mechanism deliver this sensation. The 6-speed SKYACTIV-MT is much more compact and also much lighter than comparable transmissions. Match this with a significant reduction in internal friction and fuel economy is much improved.



STAY CONNECTED. KEEP FOCUSED.

A responsive drive isn't the only thing letting you feel in sync. If your phone is connected via Bluetooth, you can check emails and have texts read out to you. It's all integrated through a central touch screen that has been positioned to help you keep your eyes focused on the road ahead. An intuitively placed rotary commander allows you to make your selections without having to look away from the road. Being able to switch menus, audio and navigation through voice command further adds to effortless control.







3-YEAR MAZDA UNLIMITED KILOMETER WARRANTY

Every Mazda is designed and built to the highest standards of performance and reliability. To give you further reassurance on how much we believe in our vehicles, our Mazda vehicles are backed up by a 3-year, Unlimited Kilometer Factory Warranty.

MAZDACARE ROADSIDE ASSISTANCE

Mazda cares about offering you peace-of-mind motoring. That is why we offer a 3-year Unlimited Roadside Assistance Plan to keep you moving every minute of the year. It includes toll-free calls and services such as free towing rescue due to minor or major mishaps and emergency medical help.

MAZDACARE SERVICE PLAN

MazdaCare has designed a Service Plan to suit your needs. It covers scheduled services for 3 years regardless of your mileage. The service plan operates alongside the Mazda Unlimited Kilometer Warranty.

Disclaimer: information and specs are based on the latest product information available at time of publication. Mazda Southern Africa (Pty) Ltd reserves the right to make changes without notice in product content and price at any time. For the latest details always contact your Mazda dealer. Coopyright subsists in this material and permission to duplicate any nart thereof should be sought from Mazda Southern Africa. Compilation date in Product the Conditions and the subsidiary of the Condition and the Conditions are not provided to the Condition and the Condition are not provided to the Condition and the Condition and the Condition are not conditions and the Condition and the Condition are not conditions an

SPECIFICATIONS

Mazda 3 Hatchback/Sedan	1.6 Original	1.6 Active	1.6 Dynamic	1.6 Dynamic Auto	2.0 Individual	2.0 Individual Auto	2.0 Astina Auto
Powertrain					O O litro in line 4 or linder	O O litro in line 4 or linder	O O litus in line 4 audio des
Engine Type	1.6 litre in-line 4 cylinder 16 valve DOHC S-VT petrol	1.6 litre in-line 4 cylinder 16 valve DOHC S-VT petrol	1.6 litre in-line 4 cylinder 16 valve DOHC S-VT petrol	1.6 litre in-line 4 cylinder 16 valve DOHC S-VT petrol	2.0 litre in-line 4 cylinder 16 valve DOHC S-VT petrol (SKYACTIV-G) with i-stop	2.0 litre in-line 4 cylinder 16 valve DOHC S-VT petrol (SKYACTIV-G) with i-stop	2.0 litre in-line 4 cylinder 16 valve DOHC S-VT petrol (SKYACTIV-G) with i-stop
Bore and stroke	78.0 x 83.6	78.0 x 83.6	78.0 x 83.6	78.0 x 83.6	83.5 x 91.2	83.5 x 91.2	83.5 x 91.2
Compression Ratio	10,0	10,0	10,0	10,0	14,0	14,0	14,0
Engine Capacity	1598 cc	1598 cc	1598 cc	1598 cc	1998 cc	1998 cc	1998 cc
Drive	2WD	2WD	2WD	2WD	2WD	2WD	2WD
Transmission	5MT	5MT	5MT	4AT	6MT	6AT	6AT
Power (kW @ rpm)	77/6000	77/6000	77/6000	77/6000	121/6000	121/6000	121/6000
Torque (Nm @ rpm)	144/4000	144/4000	144/4000	144/4000	210/4000	210/4000	210/4000
CO2 Emissions (g/km)	147/142	147/142	147/142	164/159	146/145	140/139	140/139
Emissions standard	Euro stage IV	Euro stage IV	Euro stage IV	Euro stage IV	Euro stage IV	Euro stage IV	Euro stage IV
Fuel Consumption - Combined (L/100km)*	6.2/6.0	6.2/6.0	6.2/6.0	6.9/6.7	6.2/6.1	5.9/5.8	5.9/5.8
Fuel Tank Capacity (L)	51	51	51	51	51	51	51
Transmission	5-speed manual	5-speed manual	5-speed manual	4-speed auto	6-speed manual	6-speed auto	6-speed auto
Type Gear Ratio 1st	3,416	3,416	3,416	2,816	3,363	3,552	3,552
Gear Ratio 2nd	1,842	1,842	1,842	1,553	1,947	2,022	2,022
Gear Ratio 3rd	1,218	1,218	1,218	1,000	1,300	1,452	1,452
Gear Ratio 4th	0,918	0,918	0,918	0,695	1,029	1,000	1,000
Gear Ratio 5th	0,731	0,731	0,731	-	0,837	0,708	0,708
Gear Ratio 6th	-	-	-	-	0,680	0,599	0,599
Reverse	3,214	3,214	3,214	2,279	3,385	3,893	3,893
Final drive	4,388	4,388	4,388	4,147	4,388	3,812	3,812
Chassis							
Suspension type - Front	Macpherson strut	Macpherson strut	Macpherson strut	Macpherson strut	Macpherson strut	Macpherson strut	Macpherson strut
Suspension type - Rear	Multi-link	Multi-link	Multi-link	Multi-link	Multi-link	Multi-link	Multi-link
Brake type - Front	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc
Brake type - Rear	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc	Solid disc
Diameter Front	280	280	280	280	295	295	295
Diameter Rear	265	265	265	265	265	265	265
Flacture in December Assist Otsessing	Std	Std	Std	Std	Std	Std	Std
Electronic Power Assist Steering		Ota	Ota		Ota		
Turning circle curb to curb	5,3	5,3	5,3	5,3	5,3	5,3	5,3
Turning circle curb to curb Wheels and Tyres	5,3	5,3	5,3	5,3	5,3	5,3	5,3
Turning circle curb to curb Wheels and Tyres Steel Wheels	5,3 Std	5,3	5,3 -	5,3	5,3	5,3	5,3
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels	5,3 Std	5,3 - Std	5,3 - Std	5,3 - Std	5,3 - Std	5,3 - Std	5,3 - Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size	5,3 Std - 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 215/45 R18
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size	5,3 Std - 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 215/45 R18 18X7J
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare)	5,3 Std - 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 205/60 R16	5,3 - Std 215/45 R18
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities	5,3 Std - 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16X4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 215/45 R18 18X7J 16x4T
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg)	5,3 Std - 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 205/60 R16 16X6.5J	5,3 - Std 215/45 R18 18X7J
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities	5,3 Std - 205/60 R16 16X6.5J 16X4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 205/60 R16 16X6.5J 16x4T	5,3 - Std 215/45 R18 18X7J 16x4T
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 -	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 -	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600	5,3 Std 205/60 R16 16X6.5J 16x4T 1860 1200 600	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L)	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 -	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600	5,3 Std 205/60 R16 16X6.5J 16x4T 1860 1200 600	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm)	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408	5,3 - Std 205/60 R16 16X6.5J 16X4T 1790 308/408	5,3 Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm)	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408	5,3 Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585	5,3 Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 - 308/408 4460/4585	5,3 Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408	5,3 Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm)	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795	5,3 Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795	5,3 Std 205/60 R16 16X6.5J 16X4T 1790 308/408 4460/4585 1795	5,3 Std 205/60 R16 16X6.5J 16X4T 1830 1200 600 308/408 4460/4585 1795	5,3 - Std 205/60 R16 16X6.5J 16X4T 1860 1200 600 308/408 4460/4585 1795	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm)	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450	5,3 Std 205/60 R16 16X6.5J 16X4T 1790 308/408 4460/4585 1795 1450	5,3 - Std 205/60 R16 16X6.5J 16X4T 1830 1200 600 308/408 4460/4585 1795 1450	5,3 - Std 205/60 R16 16X6.5J 16X4T 1860 1200 600 308/408 4460/4585 1795 1450	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm)	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 - 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm)	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 - 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Front overhang (mm) Rear overhang	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 Std 205/60 R16 16X6.5J 16x4T 1790 - 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Rear overhang Exterior	5,3 Std - 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Rear overhang Exterior Front fog lamps	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16X4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Rear overhang Exterior Front fog lamps Headlamps Auto on/off	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835	5,3 - Std 205/60 R16 16X6.5J 16X4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std -	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Rear overhang Exterior Front fog lamps Headlamps Auto on/off Headlamps (Halogen)	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps Auto on/off Headlamps (Halogen) Power sliding and tilt glass sunroof	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std -	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps Auto on/off Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows Power fold mirrors	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows Power fold mirrors Roof spoiler with high mounted stop lamp	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16X4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std Std Std St	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows Power fold mirrors Roof spoiler with high mounted stop lamp Rear spoiler	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps Auto on/off Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows Power fold mirrors Roof spoiler with high mounted stop lamp Rear spoiler Interior	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std	5,3 Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 - Std 205/60 R16 16X6.5J 16x4T 1790 - 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 - Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St
Turning circle curb to curb Wheels and Tyres Steel Wheels Alloy Wheels Tyre Size Wheel size Tyre Size (spare) Weights and Capacities Gross Vehicle Mass (kg) Towing mass (kg) braked Towing mass (kg) unbraked Luggage volume (L) Exterior Dimensions (mm) Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front track (mm) Rear track (mm) Front overhang (mm) Rear overhang Exterior Front fog lamps Headlamps (Halogen) Power sliding and tilt glass sunroof Power windows Power fold mirrors Roof spoiler with high mounted stop lamp Rear spoiler	5,3 Std - 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std - Std - Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1745 900 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std Std Std	5,3 - Std 205/60 R16 16X6.5J 16X4T 1790 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std - Std	5,3 - Std 205/60 R16 16X6.5J 16x4T 1830 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std Std Std St	5,3 - Std 205/60 R16 16X6.5J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St	5,3 Std 215/45 R18 18X7J 16x4T 1860 1200 600 308/408 4460/4585 1795 1450 2700 1555 1560 925 835 Std Std Std Std Std Std Std St

Mazda 3 Hatchback/Sedan	1.6 Original	1.6 Active	1.6 Dynamic	1.6 Dynamic Auto	2.0 Individual	2.0 Individual Auto	2.0 Astina Auto
Ambient temperature display	Std	Std	Std	Std	Std	Std	Std
Cargo area tonneau cover	Std	Std	Std	Std	Std	Std	Std
Cruise control	=	-	-	-	=	=	Std
Active Driving Display	-	-	-	-	-	-	Std
Door pockets (front and rear)	Std	Std	Std	Std	Std	Std	Std
Instrument panel light dimmer	Std	Std	Std	Std	Std	Std	Std
Interior illumination: cargo room lamp	Std	Std	Std	Std	Std	Std	Std
Map reading spot lamps	-	Std	Std	Std	Std	Std	Std
Leather-wrapped: gear shift knob	-	-	Std	Std	Std	Std	Std
Leather-wrapped handbrake handle	-	-	Std	Std	Std	Std	Std
Leather-wrapped steering wheel	=	-	Std	Std	Std	Std	Std
Overhead sunglass storage box	-	Std	Std	Std	Std	Std	Std
Power Lumber support (Driver side)	-	-	-	-	-	-	Std
Rear-view mirror with auto	_	_	Std	Std	Std	Std	Std
dimming function		04-1					
Seat trim- cloth	Std	Std	-	-	-	-	-
Seat trim- leather	-	-	Std	Std	Std	Std	Std
Seat- rear fold down (60:40)	Std/-	Std	Std	Std	Std	Std	Std
Seat with 8-way power adjustment (driver)	-	-	-	-	-	-	Std
Smart advanced keyless entry		-	-	-	Std	Std	Std
Smart keyless push-button engine start	Std	Std	Std	Std	Std	Std	Std
Tachometer	Digital	Digital	Digital	Digital	Digital	Digital	Analog
Electronic odometer/tripmeter	Std	Std	Std	Std	Std	Std	Std
Tilt and telescopic adjustable steering wheel	Std	Std	Std	Std	Std	Std	Std
Trip computer	Std	Std	Std	Std	Std	Std	Std
Vanity mirrors (front) with illumination	-	Std	Std	Std	Std	Std	Std
Window one touch system (driver)	Std	Std	Std	Std	Std	Std	Std
Wipers front- rain-sensing function	-	-	Std	Std	Std	Std	Std
Wiper rear with intermittent function	Std	Std	Std	Std	Std	Std	Std
Audio							
Compact display screen	Std	-	-	-	=	=	-
7 Inch display screen with commander function	-	Std	Std	Std	Std	Std	Std
Audio controls on steering wheel	Std	Std	Std	Std	Std	Std	Std
Bluetooth hands free system	-	Std	Std	Std	Std	Std	Std
Integrated navigation	-	-	-	-	=	-	Std
BOSE® Speaker type	=	-	-	-	=	=	Std
Radio/CD/AUX jack/USB	Std	Std	Std	Std	Std	Std	Std
Speaker quantity	4	6	6	6	6	6	9
Safety and Security							
Airbags SRS:driver,passenger,side & curtain	Std	Std	Std	Std	Std	Std	Std
Anti-lock Braking System (ABS)	Std	Std	Std	Std	Std	Std	Std
Blind Spot Monitoring (BSM)	-	-	-	-	-	-	Std
Burglar alarm system	Std	Std	Std	Std	Std	Std	Std
Child restraint anchor points	Std	Std	Std	Std	Std	Std	Std
Dynamic Stability Control (DSC)	-	-	-	-	Std	Std	Std
Electronic Brake-force Distribution (EBD)	Std	Std	Std	Std	Std	Std	Std
Emergency Brake Assist (EBA)	Std	Std	Std	Std	Std	Std	Std
Engine immobiliser	Std	Std	Std	Std	Std	Std	Std
Hill Launch Assist (HLA)	-	-	-	-	Std	Std	Std
Parking sensors (rear)	-	-	-	-	-	-	Std
Remote central locking (2 transmitters)	Std	Std	Std	Std	Std	Std	Std
Seat-belt warning (driver)	Std	Std	Std	Std	Std	Std	Std
Seat-belts 3-point lap-sash (all seats)	Std	Std	Std	Std	Std	Std	Std
Seat-belts (front) with pretensioners, load-limiters and height adjustable shoulder anchorages	Std	Std	Std	Std	Std	Std	Std
Side impact door beams	Std	Std	Std	Std	Std	Std	Std
Super Lock System	Std	Std	Std	Std	Std	Std	Std
MazdaCare	0.0	Old .	0.0	Old I		5.0	Old .
Service Plan	3 Years/Unlimited km	3 Years/Unlimited km					
Service intervals	15 000km	15 000km					
Warranty	3 Years/Unlimited km	3 Years/Unlimited km					
Roadside Assistance	3 Years/Unlimited km	3 Years/Unlimited km					
i iodusiuo masiatali lot	5 TODIS/OTHIT/IREU KITI	o reara/Oriminimed Kill	o reara/oriminited Kill	o roars/oriminited Kill	o roars/oriminited Kill	o roars/orinnilled KITI	5 TODIS OTHER RED KITI

